



## 22860150 EP!C - UNIVERSAL PRIMER FOR DECORATIONS



Universal quartz-based primer, ideal for new walls and old non-chalking paints. Its grain size facilitates the application of the decorative effects and creates a uniform appearance.



<b>Revision Date</b>	17/03/2017
<b>Composition</b>	Single-component, physically drying matt acrylic, water-dispersion finish paint. Classification per UNI 8681: B4.C.0.A.2.FA
<b>Main properties</b>	<ul style="list-style-type: none"><li>• it eases the application of decorative effects</li><li>• gripping agent</li></ul>
<b>Use</b>	The universal quartz-based primer is suitable for interior use on new walls or on old well-anchored non-chalking paints. Thanks to its grain, it facilitates the application of the decorative effects, creating a uniform appearance.
<b>Colour</b>	White

Technical specifications (at 20°C, 65% RH)	Reference	Unit	Value
Peso specifico (picnometro)	C022	kg/l	1,550 ± 0,050
PH	C030		8,3 ± 0,2
Viscosità Brookfield @ 200 rpm	C054	cP	2.750 ± 250
Essiccazione fuori polvere		min	5-10
Essiccazione al tatto		min	20-30
Essiccazione in profondità		ore	2-4
Sovraverniciabilità		ore	4-6

### Colour

. Surface and application conditions	Ambient temperature min +5°C / max +35°C RH < 80% Surface temperature min +5°C / max +35°C RH < 10%
. Method	Brush, roller, airless
. Diluent	Water
. Dilution	Roller 15-20%, brush 20-25%, airless 25-30%
. Mixing	Mix the product with care, adding water gradually until you reach the correct viscosity.
. Theoretical coverage	7-8 m <sup>2</sup> /l for each coat, depending on the absorbency of the surface.

Ep!c è un  
marchio di

Via del Camerario 7  
47891 Falciano, San Marino

C. o. e SM00026  
Cap. soc. € 3.000.000,00 i. v.  
Riconoscimento giuridico  
n. 26 del 20 maggio 1944

Colorificio  
Sammarinese  
SpA

T +378 (0549) 905 515  
F +378 (0549) 908 453

colorificio@colsam.com  
colsam.com



---

**Application cycle****NEW SURFACES**

The wall must be well seasoned, dry and dust free, without impurities of any kind, including loose sand or grit. Nevertheless, a coat of waterborne sealer fixative, or solvent-based sealer fixative, increases the adherence of the surface and removes chalking.

**ALREADY PAINTED SURFACES**

Remove any old loose paint by scraping and brushing it off. Also remove any tempera paint.

---

**Notes**

Any hardened drips can be easily removed with Diluente Nitro 92100012 thinner.

**Storage**

Do not allow to freeze; store at + 5°C to + 20°C. Once opened, the undiluted product can be kept for 3 months in the closed container and in the dark.

**Warnings**

Wash brushes and tools immediately after use, with water; do not dump the wash water on the ground or into groundwater.

Keep out of the reach of children.

Further information is given in the safety data sheet.

---

**VOC Classification - Directive  
2004/42/EC - Italian  
Legislative Decree 161/2006**

C/A - , maximum 40 G/L(2010).

Maximum VOC content of EP!C - FONDO UNIVERSALE PER DECORATIVI ready for use: 13.410 g/l.

---

**Specification**

Application of 2 coats of 22860150 EP!C - FONDO UNIVERSALE PER DECORATIVI , after the suitable preparation of the surfaces to be treated. Including materials and application, excluding skimming/scaffolding.

---

This information is the result of our practical experience, and is not binding. For more detailed information, please contact our technical support service. This sheet cancels and substitutes any earlier editions.

---