

TINTORETTO

Product Description

Tintoretto takes inspiration from Venetian plaster, by offering a much simpler, more cost-effective way to achieve this coveted finish at a fraction of the cost, whilst maintaining the sophistication that has come to be expected of Italian decorative finishes.

Tintoretto will create a matt feature wall with beautiful shades of colour embellished into the final effect, offering a stunning contrast that is sure to stand out.

Application Instructions

Tintoretto is ready to use and can be applied on new and old plasters, concrete surfaces, gypsum plasters, plasterboard, MDF, timber and metal surfaces after Tintoretto primer.

It can be applied by Metallic effect plastic trowel, or a Stainless-Steel Trowel. Tintoretto should not be diluted with water, but in case of extreme heat or suction, it can be diluted by water up to 5%.

Surface Preparation

Check the wall is free from dust and dirt and is as smooth as possible before starting. Correct any imperfections.

If you are planning to apply Sioloc Suede on a dusty, chalky, or high porous area, you should use Atomo (to be applied before Sioloc Suede primer). This will help to consolidate the surface.

To increase water repellency and wipeability we recommend applying 2 coats of Impera Matt.

Make sure that Tintoretto primer has been applied beforehand and that it is dry.

Mix paint well before applying as it might have settled during transport.

Apply the 1st coat of Tintoretto using the plastic trowel, or stainless-steel trowel. Avoid using linear movements, the idea is to create a random pattern using varied motions. Give this coat adequate time to dry. Begin with the 2nd coat using the same tool, continuing to repeat the varied hand movements. At this stage it is possible to be more deliberate with the pattern being created. The idea is to create intense, deep shades within this matt paint that simulate what the beauty that Venetian plaster is known for.

TINTORETTO

Cleaning of Tools

Tools should be cleaned immediately after use with water.

Technical Specifications

2KG of Tintoretto covers approx. 6 sqm depending on the thickness of the application.

Recommendations

Do not apply Tintoretto if the substrate, air, or product temperature is lower than +5C and higher than +35C, nor under direct sunlight.